

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 1 from 16

Date: 15.01.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1: Product identifier

Product form:	Mixture
Trade name:	HiKOKI Cutting oil 500ml / 1L
Unique Formula Identifier – UFI:	-
Product type:	Metalworking fluid

1.2: Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Use as cutting oil

1.3: Details of the supplier providing the safety data sheet

Manufacturer:

Koki Holdings Co. Ltd.
Shinagawa Intercity Tower A, 15-1
Konan 2-chome, Minato-ku, Tokyo, Japan

EU-Importer:

Koki Holdings Europe GmbH
Metabo-Allee 1
72622 Nürtingen, Germany

Phone:	+49 (0) 7022 - 72 0
Fax:	+49 (0) 7022 - 72 2595
Web:	https://www.hikoki-powertools.eu
E-mail:	info@hikoki-powertools.eu

1.4: Emergency number

GBK GmbH (24 h): +49 (0) 6132-84463

SECTION 2: Possible dangers

2.1: Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3; H412

Other information

Full text of hazard statements and EU hazard statements in SECTION 16.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 2 from 16

Date: 15.01.2026

2.2: Labelling elements

Hazard statements (H-phrases):

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements (P-phrases):

P273 Avoid release to the environment.

Other information

Full text of hazard statements and EU hazard statements in SECTION 16.

2.3: Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Although this product is not subject to labelling, we recommend that the safety advice be followed.

SECTION 3: Composition / information on ingredients

3.1: Substances

Not applicable

3.2: Mixtures

Mixture of base oils and additives

Composition / information on ingredients

Substance name	Product identifier	Concentration [%]	Classification according to Regulation (EC) Nr. 1272/2008 [CLP]	SCL, ATE (oral, dermal, inhalative), M-factor (acute, chronic)
Distillates (petroleum), hydrotreated heavy paraffinic	EC No. 265-169-7 Reach No. 01-2119471299-27 CAS No. 64742-65-0	≥ 60 - < 90	Asp. Tox. 1 (H304)	

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 3 from 16

Date: 15.01.2026

Zinc bis[O,O-bis(2-ethylhexyl)]bis(dithiophosphate)	EC No. 224-235-5 Reach No. 01-2119493635-27-0000 CAS No. 4259-15-8	$\geq 0,5 - < 1$	Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)	
Phenol, isopropylated, phosphate (3:1)	EC No. 273-066-3 Reach No. 01-2119535109-41 CAS No. 68937-41-7	$\geq 0,5 - < 1$	Repr. 2 (H361fd) STOT RE 2 (H373) Aquatic Chronic 2 (H411)	
2,6-di-tert-butyl-p-cresol	EC No. 204-881-4 Reach No. 01-2119565113-46-0000 CAS No. 128-37-0	$\geq 0,25 - < 0,5$	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	

3.3: Additional hints

All mineral oils used in this product contain less than 3% (w/w) DMSO extract according to IP 346 and are classified as non-carcinogenic.

Occupational exposure limits, where available, are given in section 8.

This mixture does not contain any substances in nanoform or registered as such.

SECTION 4: First aid measures

4.1: Description of first aid measures

General notes

Do not leave the affected person unattended. Immediately move the affected person away from the hazardous area and take off all contaminated clothing. In case of any doubts or symptoms immediately seek medical assistance.

After inhalation

In case of laboured or interrupted breathing immediately seek medical assistance. Provide fresh air and start first aid measures. Administer oxygen if necessary.

After skin contact

Wash the affected area thoroughly with water and soap.

After eye contact

Take out contact lenses. Thoroughly wash the open eye with water.

After ingestion

Do not induce vomiting. Consult a physician immediately. Rinse mouth thoroughly with water. Administer oxygen if necessary.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 4 from 16

Date: 15.01.2026

Protection of the first aider

Avoid all dangerous contact with the substance and take all usual precautions.

4.2: Most important symptoms and effects, both acute and delayed

No further information.

4.3: Indications of immediate medical assistance or specialised treatment

Notes for the doctor

Basic aid, decontamination, symptomatic treatment. In case of vomiting, be aware of the risk of aspiration.

Specialized treatment

No further information.

SECTION 5: Fire fighting measures

5.1: Extinguishing agent

Suitable extinguishing agents

Foam, Dry powder, Carbon dioxide (CO₂), Water mist

Unsuitable extinguishing agents

Full water jet

5.2: Special hazards arising from the substance or mixture

Hazards arising from the substance or mixture

No further information.

Hazardous combustion products

In case of fire, the following may be released: Carbon dioxide (CO₂), carbon monoxide (CO), nitrogen oxides (NO_x), smoke and other products of incomplete combustion.

5.3: Advice for firefighting

Do not breathe explosion and combustion gases. Use water spray jet to protect personnel and to cool containers in the hazard area. If safe to do so, remove undamaged containers from the hazard zone. Collect contaminated fire extinguishing water separately. Do not allow to enter the sewage system or water bodies.

Special protective equipment for firefighting

Wear self-contained breathing apparatus and chemical protective suit.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 5 from 16

Date: 15.01.2026

SECTION 6: Accidental release measures

6.1: Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid contact with skin, eyes, and clothing. In case of exposure to vapors, dusts and aerosols, use respiratory protection. Ventilate the affected area. Keep away from sources of ignition - No smoking.

6.2: Environmental protection measures

Do not allow to enter the sewage system or water bodies. Do not allow to enter the subsurface/soil. Ensure that leaks can be contained, e.g. by using drip trays or bunded areas. Inform the competent authorities in case of gas release or if the product enters water bodies, soil or the sewage system.

6.3: Methods and material for retention and cleaning

If safe to do so, stop leaks and recover spilled material. Cover drains. Prevent spread over a wide area (e.g. by bunding or using oil barriers). Clean up spills immediately. Wipe up with absorbent material (e.g. cloths, fleece). Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders). Take up mechanically and place in suitable containers for disposal. Ventilate the affected area. Thoroughly clean contaminated objects and floors in compliance with environmental regulations.

6.4: Reference to other sections

For further information on disposal, see section 13.

SECTION 7: Handling and storage

7.1: Protective measures for safe handling

Use only in well-ventilated areas. Close container with lid immediately after use. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors or mist/aerosols. Keep away from sources of ignition and heat (e.g. hot surfaces), sparks and open flames — No smoking. Do not allow to enter the sewage system or water bodies.

7.2: Conditions for safe storage considering incompatibilities

Technical measures and storage conditions

Keep container tightly closed and store in a cool (5 - 40°C), well-ventilated place. Protect containers from damage. Provide grounding for containers, equipment, pumps and suction devices. Protect against frost, heat, UV radiation/sunlight, water and moisture. Under these conditions, the product can be stored for up to 24 months.

Packaging materials

No further information.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 6 from 16

Date: 15.01.2026

Requirements for storage rooms and containers

No further information.

Instructions on storage compatibility

Storage class: 10

Substances to avoid: Oxidizing agents, food and feed.

Further information on storage conditions

No further information.

7.3: Specific end uses

Recommendations

No further information.

Specific solutions for the industrial sector (industry solutions where applicable):

No further information.

SECTION 8: Exposure controls / Personal protective equipment

The information in this section contains general advice and guidance. Information provided is based on typical anticipated uses of the product. Additional measures may be required for handling large quantities or other uses that may significantly increase worker exposure or release into the environment.

8.1: Parameters to be monitored

Occupational exposure limit values

CAS: 128-37-0

OEL (TRGS 900, Germany):

10 mg/m³ (I: inhalable fraction,
peak limitation 4[II])

DNEL values

CAS: 64742-65-0

Inhalation Long-term, local
Long-term, local

5,4 mg/m³ (worker)
1,2 mg/m³ (consumer)

CAS: 128-37-0

Dermal Long-term, systemic
Inhalation Long-term, systemic

8,3 mg/kg bw/day (worker)
5,8 mg/m³ (worker)

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 7 from 16

Date: 15.01.2026

PNEC values

CAS: 64742-65-0

PNEC – Secondary poisoning through food 9,33 mg/kg

CAS: 128-37-0

PNEC – freshwater 0,004 mg/L

PNEC – seawater 0,0004 mg/L

PNEC – sediment (freshwater) 1,29 mg/kg

PNEC – sewage treatment plant (STP) 100 mg/L

Additional notes:

The lists valid at the time of compilation served as a basis.

8.2: Exposure controls and monitoring

Suitable technical control devices

Use only in well-ventilated areas. If local exhaust ventilation is not possible or insufficient, good general ventilation of the work area should be ensured where possible. Engineering controls and the application of appropriate working procedures take precedence over the use of personal protective equipment.

Individual protective measures, for example personal protective equipment

The choice of personal protective equipment depends on the potential exposure conditions, e.g., procedures, handling methods, concentration, and ventilation. The information provided below regarding the choice of protective equipment for the use of this material is based on intended normal use.

General protective and hygienic measures

The usual precautions when managing chemicals must be observed.

Keep away from food, drink and animal feed.

Wash hands before breaks and after work.

Do not inhale gases, vapours, aerosols.

When using do not eat, drink or smoke.

Hand protection



Chemical-resistant gloves must be selected for the specific workplace depending on the concentration and quantity of the hazardous substance. Do not wear gloves near rotating machine parts or tools. Wear certified protective gloves according to DIN EN 374.

Suitable material: Nitrile rubber, Polychloroprene, Polyvinyl alcohol $\geq 0,7$ mm.

Indication of permeation breakthrough time: 6 hours

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 8 from 16

Date: 15.01.2026

Body protection

Body protection not required. If prolonged or repeated contact is likely, chemical-resistant clothing is recommended. When handling the product in drums, wear safety shoes and use appropriate equipment.

Eye and face protection



Suitable eye protection: Safety glasses with side shields according to DIN EN 166.

Breathing protection

Normally no personal respiratory protection is necessary. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection is required in case of exceeding exposure limits, insufficient ventilation or aerosol or mist formation.

Thermal protection

Take usual precautions when managing chemicals.

Further protective measures:

No further information.

Environmental exposure controls

Use a suitable container to prevent environmental contamination.

SECTION 9: Physical and chemical properties

9.1: Information on the basic physical and chemical properties

State of aggregation:	Liquid
Colour:	Yellow
Odour:	Mineral oil
pH value:	Not available
Melting point and melting range:	Not available
Initial boiling point and boiling range:	> 200°C
Pourpoint	< -10°C
Flammability:	Not available
Lower and upper explosion limit [% in air]:	0,6 – 6,5
Flash point:	196°C
Decomposition temperature:	Not available
Auto ignition temperature:	> 240°C
Vapour pressure at 20°C:	0,001 hPa
Relative vapour density:	Not available
Density at 15°C:	0,87 g/cm ³
Solubility in water:	Practically insoluble
Partition coefficient n-octanol/water:	Not available

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 9 from 16

Date: 15.01.2026

Kinematic viscosity at 40 °C:	25 mm ² /s
Evaporation number:	Not available
Explosive Properties:	Not available
Oxidising Properties:	Not available

9.2: Other information

No further information.

SECTION 10: Stability and reactivity

10.1: Reactivity

No further information.

10.2: Chemical stability

No further information.

10.3: Possibility of hazardous reactions

No further information.

10.4: Conditions to avoid

No further information.

10.5: Incompatible materials

No further information.

10.6: Hazardous decomposition products

No further information.

SECTION 11: Toxicological information

11.1: Information on hazard classes according to Regulation (EC) No. 1272/2008

Acute toxicity

There is no evidence of acute hazard from a single ingestion, skin contact, or inhalation of the product.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 10 from 16

Date: 15.01.2026

Relevant values for classification

CAS: 64742-65-0

Oral: LD50 > 5000 mg/kg (rat)

Dermal: LD50 > 5000 mg/kg (rabbit)

Inhalation: LD50 > 5,53 mg/l/4h (rat)

Corrosive/irritant effect on the skin

Not classified.

For CAS No: 64742-65-0

Slight effects, but not relevant for classification.

Severe eye damage / irritation

Not classified.

For CAS No: 64742-65-0

Slight effects, but not relevant for classification.

Sensitisation of the respiratory tract / skin

Not classified.

For CAS No: 64742-65-0

Slight effects, but not relevant for classification.

Germ cell mutagenicity

Not classified

Carcinogenicity

Not classified

Reproductive toxicity

Not classified

Specific target organ toxicity in case of single exposure

Not classified

Specific target organ toxicity in case of repeated exposure

Not classified

Aspiration hazard

Based on available data, the classification criteria for aspiration toxicity are not met. Based on the physico-chemical properties of the material. Viscosity data: see section 9.

Information on other hazards

Inhalation of dust/mist or aerosol causes irritation of the respiratory tract.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 11 from 16

Date: 15.01.2026

SECTION 12: Environmental information

12.1: Toxicity

Aquatic toxicity:

CAS: 128-37-0

LC50 > 0,57 mg/l/96h (fish)
EC50 > 0,17 mg/l/48h (aquatic invertebrates)
IC50 > 0,42 mg/l/72h (algae)

12.2: Persistence and degradability

Organic product with low water solubility. Can be largely separated mechanically in sewage treatment plants. Some of the components are biodegradable.

12.3: Bioaccumulative potential

CAS: 64742-65-0

Partition coefficient: > 3 (log Kow) (bioaccumulation)

12.4: Mobility in soil

Floats on the water surface. Is adsorbed by the soil and has low mobility.

12.5: Result of the PBT and vPvB assessment

Not applicable.

12.6: Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7: Other adverse effects

Mechanical effects of the product (e.g. sticking/clumping) may cause damage. Do not allow the product to enter the environment in an uncontrolled manner.

SECTION 13: Disposal considerations

The information in this section provides general advice and guidance. The list of identified uses in section 1 should be consulted for any application-specific information in the exposure scenarios.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 12 from 16

Date: 15.01.2026

13.1: Waste treatment process

General recommendation:

Disposal in accordance with national and local regulations. Do not allow to enter water bodies, the sewage system or the soil. In compliance with regulations and after consultation with the disposal company and the competent authority, it may be incinerated together with household waste.

Waste code number:

12 01 07*

The waste codes given are recommendations based on the expected use of this product. Due to the specific use and disposal conditions at the user's site, other waste codes may be assigned under certain circumstances. (2014/955/EU).

Designation:

Halogen-free machining oils on mineral oil basis (except emulsions and solutions).

Uncleaned packaging:

Non-contaminated and empty packaging can be recycled. Packaging that cannot be cleaned must be disposed of. Disposal in accordance with official regulations. Containers, including those that have been emptied, may contain flammable product residues and vapors. Do not cut, drill, grind, weld or perform similar activities on or near containers.

SECTION 14: Transport information

14.1: UN-Number or ID-Number

According to ADR / IMDG / IATA not a dangerous good in the sense of the transport regulations.

14.2: Proper UN-shipping name

According to ADR / IMDG / IATA not a dangerous good in the sense of the transport regulations.

14.3: Transport hazard classes

According to ADR / IMDG / IATA not a dangerous good in the sense of the transport regulations.

14.4: Packaging group

According to ADR / IMDG / IATA not a dangerous good in the sense of the transport regulations.

14.5: Environmental hazards

Indicator of environmentally hazardous substances

ADR/RID/IMDG-Code No

ICAO-TI/IATA-DGR No

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 13 from 16

Date: 15.01.2026

14.6: Special precautions for the user

No further information.

14.7: Carriage in bulk by sea in accordance with IMO instruments

No further information.

SECTION 15: Legislation

15.1: Safety, health and environmental regulations / specific legislation for the substance or mixture

CLP Regulation (EC) No 1272/2008

This product fulfils all relevant regulatory requirements.

REACH Regulation (EC) No 1907/2006

This product fulfils all relevant regulatory requirements.

RoHS Directive (2011/65/EU)

None of the substances included.

Seveso III Directive (2012/18/EU)

None of the substances included.

PIC Regulation (EU) No 649/2012

None of the substances included.

POP Regulation (EU) 2019/1021

None of the substances included.

Ozone Regulation (EC) No 1005/2009

None of the substances included.

Dual-Use Regulation (EU) 2021/821

None of the substances included.

VOC Directive 2004/42/EC

VOC content: 0%

Explosive Precursor Regulation (EU) 2019/1148

None of the substances included.

Drug Precursors Regulation (EC) No 273/2004

None of the substances included.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 14 from 16

Date: 15.01.2026

Storage class (TRGS 510)

LGK 10

Water hazard class

WGK 1 - Self-classification according to VwVwS

National regulations

Technical Instructions on Air Quality Control (TA-Luft) Weight fraction: < 0.5%

Industrial Safety Regulation (BetrSichV): Not a flammable liquid according to BetrSichV.

15.2: Chemical safety assessment

A chemical safety assessment has not been conducted.

SECTION 16: Other notes

The information is based on the present state of our knowledge but does not represent any assurance of product properties and does not establish a contractual legal relationship. The classification of the mixture was made by calculation according to the rules of Annex I in Directive 1272/2008/EU.

16.1: Notes on changes

None.

16.2: Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CAS no.	Chemical Abstract Service - Number
CLP	Regulation on classification, labelling and packaging [Regulation (EC) No 1272/2008].
DMEL	Derived exposure level with minimal impairment
DNEL	Derived exposure level without impairment
EC50/EC100	Effective Concentration, resulting in 50/100% of organisms exhibiting a defined effect
EC no.	European Community Number
EN	European Standard
EUH phrase	CLP-specific hazard statement
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
H phrase	Standardised hazard statement according to CLP/GHS
IARC	International Agency for Cancer Research

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 15 from 16

Date: 15.01.2026

IATA	Association for International Air Transport
IC50	Inhibitory concentration – concentration at which a specific biological function of organisms is inhibited by 50%
ICAO-TI	Technical instructions and guidelines by the International Civil Aviation Organisation
IMDG	Dangerous goods regulations for international maritime transport
LC/LD	Lethal concentration/dose, resulting in the death of a specified percentage of organisms
LOEC/LOEL	Lowest observed effect concentration/level, resulting in a measurable effect
M-factor	Multiplier used for environmental hazard classification
NOAEC/NOAEL	No observed adverse effect concentration/level
NOEC/NOEL	No observed effect concentration/level
OECD	Organization for Economic Co-operation and Development
OEL	Occupational exposure limit
P phrase	Standardized precautionary statement according to CLP/GHS
PBT	Persistent, bioaccumulate and toxic substance
PNEC	Estimated non-effect concentration
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals
SCL	Specific Concentration Limit
SDS	Safety data sheet
STEL	Short-term exposure limit
TRGS	Technical rules for hazardous substances
TAW	Time weighted average
RID	Regulations concerning the international carriage of dangerous goods by rail
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative

16.3: Important literature references and data sources

No further information.

16.4: Classification of mixtures and assessment method used according to Regulation (EC) No. 1272/2008 [CLP]

No further information.

16.5: Wording of H and EUH phrases (number and full text)

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Cutting oil 500ml / 1L

HiKOKI no.: 712072, 714842

Version / Language: 1.0 / EN

Site 16 from 16

Date: 15.01.2026

H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6: Full text of the classifications [CLP/GHS]

Asp. Tox. 1:	Aspiration hazard, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – acute hazard, Category 1
Aquatic Chronic 2:	Hazardous to the aquatic environment – chronic hazard, Category 2
Aquatic Chronic 3:	Hazardous to the aquatic environment – chronic hazard, Category 3
Eye Dam. 1:	Serious eye damage, Category 1
STOT RE 2:	Specific target organ toxicity (repeated exposure), Category 2
Repr. 2:	Reproductive toxicity, Category 2

16.7: Training advice

No further information.

16.8: Additional information

No further information.

Note for the reader:

To the best of our knowledge, the information contained here is correct. However, neither the above-named manufacturer nor its affiliates assume any liability as to the accuracy or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described here, we cannot guarantee that these are the only possible risks.