

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 1 from 19

Date: 15.01.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1: Product identifier

Product form:	Mixture
Trade name:	HiKOKI Resin solvent 400 ml
Unique Formula Identifier – UFI:	DVGM-2KER-SN03-EPH2
Product type:	Cleaning agent

1.2: Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

SU21 Consumer product. PC35 Cleaning agent. Other vehicle (all types) cleaning and care products.

1.3: Details of the supplier providing the safety data sheet

Manufacturer:

Koki Holdings Co. Ltd.
Shinagawa Intercity Tower A, 15-1
Konan 2-chome, Minato-ku, Tokyo, Japan

EU-Importer:

Koki Holdings Europe GmbH
Metabo-Allee 1
72622 Nürtingen, Germany

Phone: +49 (0) 7022 - 72 0
Fax: +49 (0) 7022 - 72 2595
Web: <https://www.hikoki-powertools.eu>
E-mail: info@hikoki-powertools.eu

1.4: Emergency number

GBK GmbH (24 h): +49 (0) 6132-84463

SECTION 2: Possible dangers

2.1: Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosols, category 1. Eye irritation, category 2. Specific target organ toxicity after single exposure, category 3.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 2 from 19

Date: 15.01.2026

Other information

Full text of hazard statements and EU hazard statements in SECTION 16.

2.2: Labelling elements

Hazard pictograms:



Signal word: Danger

Hazard statements (H-phrases):

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements (P-phrases):

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P410	Protect from sunlight.
P412	Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an official chemical waste depot.

Supplemental Hazard Information:

Contains: Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; Propan-2-ol.

Other information

The classification of this product is based on the non-aerosolised form of the mixture (on basis of section 1.1.3.7. of Regulation (EC) No 1272/2008).

Full text of hazard statements and EU hazard statements in SECTION 16.

2.3: Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 3 from 19

Date: 15.01.2026

SECTION 3: Composition / information on ingredients

3.1: Substances

Not applicable

3.2: Mixtures

Composition / information on ingredients

Substance name	Product identifier	Concentration [%]	Classification according to Regulation (EC) Nr. 1272/2008 [CLP]	SCL, ATE (oral, dermal, inhalative), M-factor (acute, chronic)
Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC No. 919-857-5 Reach No. 01-2119463258-33 CAS No. -	75 - < 100	Flam. Liq. 3 (H226); Asp. Tox. 1 (H304); STOT SE 3 (H336)	
Propan-2-ol	EC No. 200-661-7 Reach No. 01-2119457558-25 CAS No. 67-63-0	10 - < 25	Flam. Liq. 2 (H225); Eye Irrit. 2 (H319); STOT SE 3 (H336)	
Carbon dioxide	EC No. 204-696-9 Reach No. - CAS No. 124-38-9	2,5 - < 10	Press. Gas (H280)	
Reaction mass of ethylbenzene and xylene	EC No. 905-588-0 Reach No. 01-2119488216-32 CAS No. -	2,5 - < 10	Flam. Liq. 3 (H226); Asp. Tox. 1 (H304); Acute Tox. 4 (H312, H332); Skin Irrit. 2 (H315); Eye Irrit. 2 (H319); STOT SE 3 (H373); STOT RE 2 (H335)	

3.3: Additional hints

Occupational exposure limits, where available, are given in section 8.

This mixture does not contain any substances in nanoform or registered as such.

SECTION 4: First aid measures

4.1: Description of first aid measures

General notes

Do not leave the affected person unattended. Immediately move the affected person away from the hazardous area and take off all contaminated clothing. In case of any doubts or symptoms immediately seek medical assistance.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 4 from 19

Date: 15.01.2026

After inhalation

In case of laboured or interrupted breathing immediately seek medical assistance. Provide fresh air and start first aid measures.

After skin contact

Take off contaminated clothing. Wash the affected area thoroughly with water and soap. Consult a doctor if irritation persists.

After eye contact

Take out contact lenses. Thoroughly wash the open eye with water.

After ingestion

Aerosol or mist: Ingestion is unlikely to occur.

Protection of the first aider

Avoid all dangerous contact with the substance and take all usual precautions.

4.2: Most important symptoms and effects, both acute and delayed

Inhalation:	May cause headache, drowsiness, dizziness and a feeling of sickness. May cause irritation to respiratory airways and coughing.
Skin contact:	Repeated exposure may cause skin dryness or cracking.
Eye contact:	Irritant. May cause redness and pain.
Ingestion:	Aerosol or mist: Ingestion is unlikely to occur.

4.3: Indications of immediate medical assistance or specialised treatment

Notes for the doctor

No further information.

Specialized treatment

No further information.

SECTION 5: Fire fighting measures

5.1: Extinguishing agent

Suitable extinguishing agents

Carbon dioxide (CO₂). Alcohol resistant foam. Dry chemical. Water fog.

Unsuitable extinguishing agents

Water jet. Use of heavy stream of water may spread fire.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 5 from 19

Date: 15.01.2026

5.2: Special hazards arising from the substance or mixture

Hazards arising from the substance or mixture

Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50°C. Do not expose emergency personnel to overheated aerosol containers. Water may be used to cool container and prevent explosion of the aerosol.

Hazardous combustion products

Carbon monoxide may be evolved if incomplete combustion occurs.

5.3: Advice for firefighting

Fight a fire where aerosols are involved from a protected position.

Special protective equipment for firefighting

Use adequate respiratory equipment in case of insufficient ventilation.

SECTION 6: Accidental release measures

6.1: Personal precautions, protective equipment and emergency procedures

Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Vapours are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

6.2: Environmental protection measures

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3: Methods and material for retention and cleaning

Collect spilled material in containers. Absorb residues in sand or other inert material. Collect aerosol cans in an approved container. Do not pierce aerosols. Wash away remainder with plenty of water and soap.

6.4: Reference to other sections

For further information on disposal, see section 13.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 6 from 19

Date: 15.01.2026

SECTION 7: Handling and storage

7.1: Protective measures for safe handling

Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

7.2: Conditions for safe storage considering incompatibilities

Technical measures and storage conditions

Keep away from oxidizing agents. Keep frost-free, in a cool (< 35°), dry and well-ventilated place. Protect from sunlight and keep away from heat.

Instructions on storage compatibility

Storage class: 2B

Substances to avoid: Oxidising agents

Further information on storage conditions

No further information.

7.3: Specific end uses

Recommendations

Use only as directed. Do not mix with other products.

SECTION 8: Exposure controls / Personal protective equipment

The information in this section contains general advice and guidance. Information provided is based on typical anticipated uses of the product. Additional measures may be required for handling large quantities or other uses that may significantly increase worker exposure or release into the environment.

8.1: Parameters to be monitored

Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have not been established for this product.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 7 from 19

Date: 15.01.2026

Occupational exposure limit values

Substance: Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

TWA 8 hour: 1200 mg/m³ (Basis: CEFIC-HSPA)

STEL 15 min: -

Substance: Propan-2-ol

TWA 8 hour: 999 mg/m³ (Basis GB: MAC [UK])

STEL 15 min: 1250 mg/m³ (Basis GB: MAC [UK])

Substance: Carbon dioxide

TWA 8 hour (GB): 9150 mg/m³ (Basis GB: MAC [UK])

STEL 15 min (GB): 27400 mg/m³ (Basis GB: MAC [UK])

TWA 8 hour (EC): 9000 mg/m³ (Basis EC: Directive 2006/15/EG)

DNEL values

Substance: Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral Long-term, systemic 46 mg/kg bw/day (consumer)

Dermal Long-term, systemic 77 mg/kg bw/day (worker)
Long-term, systemic 46 mg/kg bw/day (consumer)

Inhalation Long-term, systemic 871 mg/m³ (worker)
Long-term, systemic 185 mg/m³ (consumer)

Substance: Propan-2-ol

Oral Long-term, systemic 26 mg/kg bw/day (consumer)

Dermal Long-term, systemic 888 mg/kg bw/day (worker)
Long-term, systemic 319 mg/kg bw/day (consumer)

Inhalation Long-term, systemic 500 mg/m³ (worker)
Long-term, systemic 89 mg/m³ (consumer)

Substance: Reaction mass of ethylbenzene and xylene

Oral Long-term, systemic 12,5 mg/kg bw/day (consumer)

Dermal Long-term, systemic 212 mg/kg bw/day (worker)
Long-term, systemic 125 mg/kg bw/day (consumer)

Inhalation Long-term, systemic / local 221 mg/m³ (worker)
Short-term, systemic / local 442 mg/m³ (worker)
Long-term, systemic / local 65,3 mg/m³ (consumer)
Short-term, systemic / local 260 mg/m³ (consumer)

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 8 from 19

Date: 15.01.2026

PNEC values

Substance: Propan-2-ol

PNEC – freshwater	140,9 mg/L
PNEC – seawater	140,9 mg/L
PNEC – sediment (freshwater)	552 mg/kg
PNEC – sediment (seawater)	552 mg/kg
PNEC – sewage treatment plant (STP)	2251 mg/L
PNEC – soil	28 mg/kg
PNEC – Secondary poisoning through food	160 mg/kg food

Substance: Reaction mass of ethylbenzene and xylene

PNEC – freshwater	0,327 mg/L
PNEC – seawater	0,327 mg/L
PNEC – sediment (freshwater)	12,46 mg/kg
PNEC – sediment (seawater)	12,46 mg/kg
PNEC – sewage treatment plant (STP)	6,58 mg/L
PNEC – soil	2,31 mg/kg

Additional notes:

The lists valid at the time of compilation served as a basis.

8.2: Exposure controls and monitoring

Suitable technical control devices

Use only in well-ventilated areas. Comply with standard precautionary measures for working with chemicals.

Individual protective measures, for example personal protective equipment

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the local situation.

General protective and hygienic measures

The usual precautions when managing chemicals must be observed.

Keep away from food, drink and animal feed.

Wash hands before breaks and after work.

Do not inhale gases, vapours, aerosols.

When using do not eat, drink or smoke.

Hand protection



Under normal conditions of use specific gloves are not required. Wear appropriate gloves in case of frequent or prolonged use and in case of large-scale exposure.

Suitable material: nitril. $\pm$ 0,5 mm.

Indication of permeation breakthrough time not known.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 9 from 19

Date: 15.01.2026

Body protection

Use of specific protective industrial clothing is not required under normal conditions of use. In case of large-scale exposure wear suitable protective clothing, overalls or suit, and similar boots.

Suitable material: nitril. $\pm 0,5$ mm.

Eye and face protection



Wear appropriate safety glasses with side shields, in accordance with EN 166, when there is danger of possible eye contact.

Breathing protection

Take care of sufficient ventilation. Wear suitable respiratory protection in case of large-scale exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance with EN 140.

Thermal protection

Take usual precautions when managing chemicals.

Further protective measures:

No further information.

Environmental exposure controls

Use a suitable container to prevent environmental contamination.

SECTION 9: Physical and chemical properties

9.1: Information on the basic physical and chemical properties

Physical state:	Aerosol
Colour:	Colourless
Odour:	Characteristic
pH value:	Not available (Waterfree product)
Melting point and melting range:	Not available
Initial boiling point and boiling range:	Not available
Flammability:	Extremely flammable ($\geq 85\%$ flam. comp. and heat combustion ≥ 30 kJ/g)
Lower and upper explosion limit [% in air]:	0,6 - 12
Flash point:	Not available
Decomposition temperature:	Aerosol explodes before reaching decomp. temp.
Auto ignition temperature:	Not available
Vapour pressure at 20°C:	5 bar
Relative vapour density:	Not available
Relative density at 20°C:	0,794 g/ml
Solubility in water:	Active ingredients not soluble. Propellant(s) soluble.
Partition coefficient n-octanol/water:	Not available

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 10 from 19

Date: 15.01.2026

Kinematic viscosity at 40 °C:

Not available

Evaporation number:

Not available

Explosive Properties:

Pressurised container: May burst if heated.

Oxidising Properties:

Does not contain oxidizing substances.

9.2: Other information

No further information.

SECTION 10: Stability and reactivity

10.1: Reactivity

No further information.

10.2: Chemical stability

No further information.

10.3: Possibility of hazardous reactions

No further information.

10.4: Conditions to avoid

Keep away from sources of ignition and sources of heat.

10.5: Incompatible materials

No further information.

10.6: Hazardous decomposition products

No further information.

SECTION 11: Toxicological information

11.1: Information on hazard classes according to Regulation (EC) No. 1272/2008

Acute toxicity

No toxicological research has been carried out on this product.

Inhalation of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 11 from 19

Date: 15.01.2026

Calculated LD50 (Oral):	1812 mg/kg.bw. –	Not classified.
Calculated LD50 (Dermal):	5000 mg/kg.bw. –	Not classified.
Calculated LC50 (Inhalation):	10 mg/l –	Not classified.

Relevant values for classification

Substance: Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral: NOAEL > 1000 mg/kg/24h (rat) - estimate

Dermal: LD50 > 5000 mg/kg (rat) - estimate

Inhalation: LC50 > 5000 mg/m³ (rat) – estimate
NOAEL > 1160 mg/m³ (rat) - estimate

Substance: Propan-2-ol

Oral: LD50 5840 mg/kg (rat)
NOAEL 870 mg/kg/24h (rat)

Dermal: LD50 12800 mg/kg (rat)

Inhalation: LC50 46600 mg/m³ (rat)
NOAEL 12500 mg/m³ (rat)

Substance: Reaction mass of ethylbenzene and xylene

Oral: LD50 > 2000 mg/kg (rat) - estimate
NOAEL 250 mg/kg/24h (rat) – estimate

Dermal: LD50 > 2000 mg/kg (rat) - estimate

Inhalation: NOAEL 3515 mg/m³ (rat) - estimate
LC50 > 5000 mg/m³ (rat) - estimate

Corrosive/irritant effect on the skin

Not classified. Slight irritation possible. Repeated exposure may cause skin dryness or cracking. Prolonged contact may dry out and defat the skin.

Severe eye damage / irritation

Irritant.

Sensitisation of the respiratory tract / skin

Not classified. May cause irritation to respiratory airways and coughing

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 12 from 19

Date: 15.01.2026

Germ cell mutagenicity

Not classified. Does not contain mutagenic substances.

Carcinogenicity

Not classified

Reproductive toxicity

Not classified

Specific target organ toxicity in case of single exposure

Not classified

Specific target organ toxicity in case of repeated exposure

Not classified

Aspiration hazard

Not classified

Information on other hazards

No further information.

SECTION 12: Environmental information

12.1: Toxicity

No ecotoxicological research has been carried out on this product. The values are calculated.

Aquatic toxicity:

Contains 0 % of components with unknown hazards to the aquatic environment.

May form an oil film on the water surface causing a decline in oxygen content with possible adverse effects for aquatic organisms.

LC50 62 mg/l (fish)

EC50 79 mg/l (waterflea)

12.2: Persistence and degradability

No further information.

12.3: Bioaccumulative potential

No further information.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 13 from 19

Date: 15.01.2026

12.4: Mobility in soil

No further information.

12.5: Result of the PBT and vPvB assessment

Not applicable.

12.6: Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7: Other adverse effects

No further information.

SECTION 13: Disposal considerations

The information in this section provides general advice and guidance. The list of identified uses in section 1 should be consulted for any application-specific information in the exposure scenarios.

13.1: Waste treatment process

General recommendation:

Must be given special treatment in compliance with official regulations.

Must not be disposed of together with household waste. Do not dispose of into the environment, drains, sewers or water courses. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

European Waste Catalogue:

Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Uncleaned packaging:

Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat product residues and non-empty pack as hazardous waste.

SECTION 14: Transport information

14.1: UN-Number or ID-Number

UN 1950. For IATA only: ID 8000

14.2: Proper UN-shipping name

AEROSOLS. For IATA only: CONSUMER COMMODITY

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 14 from 19

Date: 15.01.2026

14.3: Transport hazard classes

ADR:

Class:	2
Classification code:	5F
Packaging group:	-
Danger label:	2,1
Tunnel restriction code:	D
Other information:	Not intended for carriage by tank-vessels on inland waterways.



IMDG:

Class:	2,1
Packaging group:	-
EmS (fire / spill):	F - D / S - U
Marine pollutant:	No

IATA:

Class:	2,1
ERG code:	10L

14.4: Packaging group

No further information.

14.5: Environmental hazards

Indicator of environmentally hazardous substances

ADR/RID/IMGD-Code	No
ICAO-TI/IATA-DGR	No

14.6: Special precautions for the user

Country specific variations may apply. It is possible that a "Limited Quantity" exemption applies to the transport of this product. An IATA ID8000 Consumer Commodity package must bear an Air Limited Quantity marking and a Class 9 hazard label.

14.7: Carriage in bulk by sea in accordance with IMO instruments

Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments. Packaged liquids are not considered bulk.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 15 from 19

Date: 15.01.2026

SECTION 15: Legislation

15.1: Safety, health and environmental regulations / specific legislation for the substance or mixture

CLP Regulation (EC) No 1272/2008

This product fulfils all relevant regulatory requirements.

This product is exempted from classification as "May be fatal if swallowed and enters airways" on basis of section 3.10.1.6.3. of Annex I

REACH Regulation (EC) No 1907/2006

This product fulfils all relevant regulatory requirements.

Aerosol Dispenser Directive 75/324/EEC

This product fulfils all relevant regulatory requirements.

Directive 2008/98/EC (Waste Framework Directive)

This product fulfils all relevant regulatory requirements.

Regulation (EC) No 648/2004 on detergents

Contains Aliphatic hydrocarbons: > 30% concentration

Contains: Aromatic hydrocarbons: < 5% concentration

RoHS Directive (2011/65/EU)

None of the substances included.

Seveso III Directive (2012/18/EU)

None of the substances included.

PIC Regulation (EU) No 649/2012

None of the substances included.

POP Regulation (EU) 2019/1021

None of the substances included.

Ozone Regulation (EC) No 1005/2009

None of the substances included.

Dual-Use Regulation (EU) 2021/821

None of the substances included.

VOC Directive 2010/75/EU

VOC content: 75 - < 100%

(calculated based on hydrocarbons and organic propellants)

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 16 from 19

Date: 15.01.2026

Explosive Precursor Regulation (EU) 2019/1148

None of the substances included.

Drug Precursors Regulation (EC) No 273/2004

None of the substances included.

Storage class (TRGS 510)

LGK 2B

Water hazard class

WGK 1 - Self-classification according to AwSV

Specific National Requirements (United Kingdom)

To comply with UK safety standards for aerosols, the back label shall include the warning badge 'Solvent Abuse Can Kill Instantly' along with the instructional phrase 'Use only as directed' to warn against volatile solvent abuse.

15.2: Chemical safety assessment

A chemical safety assessment has not been conducted.

SECTION 16: Other notes

The information is based on the present state of our knowledge but does not represent any assurance of product properties and does not establish a contractual legal relationship. The classification of the mixture was made by calculation according to the rules of Annex I in Directive 1272/2008/EU.

16.1: Notes on changes

None.

16.2: Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CAS no.	Chemical Abstract Service - Number
CLP	Regulation on classification, labelling and packaging [Regulation (EC) No 1272/2008].
DMEL	Derived exposure level with minimal impairment
DNEL	Derived exposure level without impairment
EC50/EC100	Effective Concentration, resulting in 50/100% of organisms exhibiting a defined effect
EC no.	European Community Number

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 17 from 19

Date: 15.01.2026

EN	European Standard
EUH phrase	CLP-specific hazard statement
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
H phrase	Standardised hazard statement according to CLP/GHS
IARC	International Agency for Cancer Research
IATA	Association for International Air Transport
ICAO-TI	Technical instructions and guidelines by the International Civil Aviation Organisation
IMDG	Dangerous goods regulations for international maritime transport
LC/LD	Lethal concentration/dose, resulting in the death of a specified percentage of organisms
LOEC/LOEL	Lowest observed effect concentration/level, resulting in a measurable effect
M-factor	Multiplier used for environmental hazard classification
NOAEC/NOAEL	No observed adverse effect concentration/level
NOEC/NOEL	No observed effect concentration/level
OECD	Organization for Economic Co-operation and Development
OEL	Occupational exposure limit
P phrase	Standardized precautionary statement according to CLP/GHS
PBT	Persistent, bioaccumulate and toxic substance
PNEC	Estimated non-effect concentration
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals
SCL	Specific Concentration Limit
SDS	Safety data sheet
STEL	Short-term exposure limit
TRGS	Technical rules for hazardous substances
TAW	Time weighted average
RID	Regulations concerning the international carriage of dangerous goods by rail
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative

16.3: Important literature references and data sources

No further information.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 18 from 19

Date: 15.01.2026

16.4: Classification of mixtures and assessment method used according to Regulation (EC) No. 1272/2008 [CLP]

No further information.

16.5: Wording of H and EUH phrases (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6: Full text of the classifications [CLP/GHS]

Aerosol 1:	Aerosols, category 1
Press. Gas (Comp.):	Gases under pressure: Compressed gas
Flam. Liq. 2:	Flammable liquids, category 2
Flam. Liq. 3:	Flammable liquids, category 3
Asp. Tox. 1:	Aspiration hazard, category 1
Acute Tox. 4:	Acute toxicity, category 4
Skin Irrit. 2:	Skin irritation, category 2
Eye Irrit. 2:	Eye irritation, category 2
STOT SE 3:	Specific target organ toxicity after single exposure, category 3
STOT RE 2:	Specific target organ toxicity after single exposure, category 2

16.7: Training advice

No further information.

Safety data sheet

according to Regulation (EC) No 1907/2006 (REACH)



Trade name: HiKOKI Resin solvent 400 ml

HiKOKI no.: 714841

Version / Language: 1.0/EN

Site 19 from 19

Date: 15.01.2026

16.8: Additional information

No further information.

Note for the reader:

To the best of our knowledge, the information contained here is correct. However, neither the above-named manufacturer nor its affiliates assume any liability as to the accuracy or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described here, we cannot guarantee that these are the only possible risks.